


SEPARATOR MATERIAL, ITS MANUFACTURING METHOD AND CELL INCORPORATING ABOVE

Patent number: JP2003031200
Publication date: 2003-01-31
Inventor: YAMAMOTO HIROYUKI; AOKI NOBUO; TANAKA TOMOFUMI; KIDA TATSUNOBU; KAMISASA TOSHIO
Applicant: DAIWA SPINNING CO LTD;; DAIWABO POYTECH KK
Classification:
- international: H01M2/16; D21H13/14; D21H15/10; D21H25/02; D21H25/04; H01M10/30; H01M10/40
- european:
Application number: JP20020134579 20020509
Priority number(s): JP20010138796 20010509; JP20020134579 20020509

Report a data error here

Abstract of JP2003031200

PROBLEM TO BE SOLVED: To provide a separator material and a cell incorporating above which can operate a split process without inducing a fiber ball phenomenon in a defibrating process when a wet paper-making web is made, has a good density of nonwoven fabric and uniformity of formation, does not inhibit passing of electrolyte solution of gas, has good liquid keeping property and has a good cell property. **SOLUTION:** The separator material is composed of wet nonwoven fabric which includes a range of not less than 5 mass% and not more than 75 mass% separate type conjugated fiber structured with a plurality of different components of polyolefin system resin, and other polyolefin system fibers of not more than 25 mass% to not less than 95 mass% with fineness range of not less than 0.1 dtex to not more than 3 dtex. At least a part of the separate type conjugated fiber is divided to form a very fine fiber of fineness of less than 0.5 dtex having a nearly trapezoid-shaped fiber cross section, and is hydrophilized.



Data supplied from the esp@cenet database - Worldwide